Fujitsu recommends Windows 8 Pro.

Data Sheet
Fujitsu ESPRIMO E910 0-Watt Desktop PC

The Innovative 0-Watt PC

Fujitsu ESPRIMO E910 PCs give you the absolute highest PC manageability, performance and expandability. These Zero Noise PCs help you focus on your work and with 94% efficient power supply with 0-Watt technology, you'll also save on energy costs. The use of identical components ensures perfect infrastructure compatibility. At retirement, Fujitsu's distinctive EraseDisk function wipes your data securely.

0-Watt PC
Cost savings by completely reducing off-mode losses
- Patented function for 0-Watt power consumption in off mode with simultaneous management in a time slot that can be optionally set

Zero Noise PC
Pleasant working environment due to completely quiet system (solid state disk required)
- Fan stop in standard operations

Green technology
Fujitsu's contribution to environmental protection for the continued existence of our planet
- Halogen-free printed circuit mainboard and power supply, sophisticated product concept for the entire lifecycle

Energy efficiency coupled with intelligent performance
The best-in-class regarding power consumption combined with new levels of performance
- 3rd generation Intel® Core™ processor family, a switched monitor outlet and a power supply with up to 94% efficiency

System management
Simple system administration for complex IT infrastructures
- Intel® vPro™ technology (depending on processor) and DeskView manageability tools

Fujitsu recommends Windows 8 Pro.

Components

Processor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) *
	Intel® Core™ i5-3570 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Pentium® processor G2120 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2020 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G1610 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics)
	Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
	Intel® Core™ Processor with Intel® Small Business Advantage - Smart Platform for Unmanaged Small Business
Operating systems	
Operating system	Windows 8 Pro Windows 8 Windows® 7 Professional 64-bit Windows® 7 Professional 32-bit Windows® 7 Home Premium 64-bit Windows® 7 Home Basic 32-bit (EM)
Operating system compatible	openSUSE Linux Windows® XP Citrix XenClient™ 2
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Hard disk drives (internal)	SSD SATA III Premium, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch, SED
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 250 GB, 3.5-inch
	HDD SATA II, 7,200 rpm, 320 GB, 2.5-inch
	HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch
Graphics	NVIDIA® NVS 300 LP, 512 MB
	NVIDIA® GeForce® GT630 DisplayPort 2GB LP "0-Watt", 2 GB
	NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB
	LFH59/ 2x DVI-I adapter cable
	LFH59/ 2x DP adapter cable
	DVI to VGA Adapter
	DP to DVI-D (single link) Adapter Cable
	2nd NVIDIA® Quadro® NVS 300 LP, 512 MB

Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only, not for Indonesia)
	Parallel Interface
	Gigabit Ethernet PCIe x1, DS
	eSATA Interface
	Dual serial card PCIe x1, powered
	Dual serial card PCIe x1
Base unit	ESPRIMO E910 0-Watt
Mainboard	
Mainboard type	D3162
Formfactor	µATX
Chipset	Intel® Q77
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1,600 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	6
thereof SATA III	2
thereof eSATA	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 (Windows XP not supported) Intel® Smart Response Technology (depending on CPU)
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	10
USB 3.0 total	4
USB front	4x 2.0 or 2x 2.0/ 2x 3.0 (optional)
USB rear	6x 2.0 / 2x 3.0

Interfaces	
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	2 (optional)
Interface Module notes	Anytime USB charge functionality
Input device / components	
	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO
Drive bays	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"
Slots	
PCI-Express 3.0 x16	1 x (200 mm / 7.87 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (200 mm / 7.87 inch) Low profile
PCI-Express x1	1 x (174 mm / 6.85 inch) Low profile
PCI (32-bit / 33 MHz)	1 x (174 mm / 6.85 inch) Low profile
Slots optional configuration	or 2x PCI full high via Riser
Graphics on board	
Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1,759 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DVI)	1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel

Graphics on board	
Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL® 1.1 (depending on CPU) For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows® 7 or Windows 8)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 91% / 94% / 92%
	0-Watt mode automatically
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched
Power consumption	
Power consumption note	See white paper Energy Consumption 0-Watt mode automatically
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=a85c872e-6bb9-4e66-95b3-f106e65fde61
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise emission	
Related Processors for noise	Core i5-3770
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.6 B / 23 dB(A) Bystander ; 26 dB(A) Operator position
Standard noise operation mode: HDD load	3.3 B / 20 dB(A) Bystander ; 24 dB(A) Operator position
Standard noise operation mode: Idle mode	SSD: no noise emmision, 2.5" HDD: 3.1 B / 18 dB(A) Bystander ; 20 dB(A) Operator position, 3.5" HDD: 3.2 B / 19 dB(A) Bystander ; 22 dB(A) Operator position
Standard noise operation mode: ODD load	4.6 B / 32 dB(A) Bystander ; 38 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	SSD: no noise emmision, 2.5" HDD: 3.1 B / 18 dB(A) Bystander ; 20 dB(A) Operator position, 3.5" HDD: 3.2 B / 20 dB(A) Bystander ; 23 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level Lwad (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.8 B = 38 dB
Blue angel noise operation mode: Idle mode	3.7 B = 37 dB
Blue angel noise operation mode: ODD load	4.7 B = 47 dB

Dimensions / Weight / Environmental	
Dimensions (W x D x H)	340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	10 kg
Weight (lbs)	22.05 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Compliance	
Product	ESPRIMO E910
Model	DT8
Germany	TÜV GS Blauer Engel / Blue Angel
Europe	CE Nordic Swan
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 (dedicated regions) EPEAT® Gold (dedicated regions)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) Anti Virus software (60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL
Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime
Compatibility (references)	
	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 8.0 (depending on CPU) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform

Manageability	
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
System and BIOS Security	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
Serviceability	
	EasyFix EasyChange for 3.5" HDD EasyChange for optical drives
Packaging information	
Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (lbs) Carton	2.51 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	3 years (depending on country)
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 2 years material warranty)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Maintenance and Support Services - the perfect extension	
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Mouse M440 ECO		Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.	Order Code: S26381-K450-L200
SOUNDSYSTEM DS E2000 Air		The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600
HS E2000 Communicator Headset		The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.	Order Code: S26391-F7139-L5
Keyboard KBPC PX ECO		Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.	S26381-K341-L1** (**: country specific variation)

Fujitsu recommends Windows 8 Pro.

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO E910 0-Watt, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E910 0-Watt, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2014-01-27 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions